

## CLAIMS

We claim:

1. An eccentrically oscillating gear device comprising:  
an internal gear having internal gear pins on an inner periphery thereof;  
5 a carrier rotatable relatively to the internal gear;  
a pair of bearings having a rolling element and a ring body for supporting the rolling  
element and disposed between an outer periphery of the carrier and the inner periphery of the  
internal gear;  
a crank shaft freely rotatably mounted on the carrier; and  
10 an external gear equipped with external teeth having a trochoid tooth profile on an  
outer periphery thereof in which tooth top portions of the external teeth are cut out, engaged with the  
internal gear pins on the outer periphery thereof, fitted to a crank portion of the crank shaft and  
disposed between the pair of bearings,  
wherein the external gear makes an eccentrically oscillating motion by rotation of the  
15 crank shaft so that a rotational output is taken out from the internal gear or the carrier,  
characterized in that receiving portions for receiving end portions of the internal gear  
pins are formed at end surface portions of an external-gear side of the pair of bearings, and the  
internal gear pins are supported by the receiving portions, thereby regulating movement of the  
internal gear pins to a carrier side.  
20
2. The eccentrically oscillating gear device according to claim 1, wherein a ring body of  
the pair of bearings is equipped with an outer race and an inner race, and the receiving portions are  
formed on the outer race or the inner race.